

●機型代碼 ○：油壓式 E:伺服馬達型 D:安全門 M:人機介面 A:上下自動拆/裝型 B:後面進模

配備		機台系列														
		4020系列	5940-Air系列	5940-O系列	7035系列	7550-O系列	7550-E系列	7550-EB系列	7560系列	8060系列	10050系列	11040系列	12050系列	120110系列	17050系列	22080系列
作動模式	熱模板	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	上/下模板	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
鎖模模式	熱模板	●	●	●	●(油壓)	●(空壓)	●(空壓)	●(空壓)	●	●	●(油壓)	●	●	●	●	●
	上模板	●	●	●	●(油壓)	●(空壓)	●(空壓)	●	●	●	●(油壓)	●	●	●	●	●
	下模板	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		●	●	●	●(空壓)	●(空壓)	●(空壓)	●	●	●	●(空壓)	●	●	●	●	●
線路控制	PLC	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	蓄電池	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
操作面板	按鈕	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	人機介面	●	●	●	●(7")	●(10")	●(10")	●	●(7")	●(7")	●(7")	●	●	●	●(7")	●
安全網	安全光幕	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	安全門(空壓)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
溫度顯示器	面版顯示	2組(上下各1)	2組(上下各1)	2組(上下各1)	4組(上下各2)	4組(上下各2)	●(上下各4組)	●(上下各4組)	●(上下各1)	●(上下各2組)	●(上下各2組)	●(上下各2)	●(上下各2)	●(上下各4)	●(上下各4)	●(上下各7)
	PLC	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
真空模式	最大功率	4000W	4000W	4000W	4000W	4000W	4000W	4000W	4000W	4000W	4000W	4000W	4000W	4000W	4000W	4000W
	氣壓式產生器	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
模具參數式	ID編號	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	編號搜尋	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
防呆裝置	參數儲存數	●	●	●	10組	●	●	●	●	●	●	●	●	●	●	●
	上下模無料檢知	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	汽源檢知器	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	真空檢知器	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
壓力調整	自動接電器/氣管點	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	手動	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
自動(拆/裝)裝置	前面拆裝	●	●	●	●(上下模組)	●	●	●	●	●	●	●	●	●	●	●
	後面拆裝	●	●	●	●(熱模組)	●	●	●	●	●	●	●	●	●	●	●
上下模自動(拆/裝)裝置	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
熱模自動(拆/裝)裝置	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
斷電油缸歸位系統	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
強制抽煙風扇(排煙管口6")	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
上模防掉裝置	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
上/下伺服馬達容量	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
熱模伺服馬達容量	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
上汽缸最大輸出力	300kg	300kg	300kg	●	●	●	●	●	●	●	●	●	●	●	●	●
下汽缸最大輸出力	470kg	470kg	470kg	●	●	●	●	●	●	●	●	●	●	●	●	●
上油缸最大輸出力	●	●	●	600kg	600kg	600kg	600kg	600kg	600kg	950kg	600kg	950kg	1500kg	1500kg	1500kg	1500kg
下油缸最大輸出力	●	●	●	600kg	600kg	600kg	600kg	600kg	600kg	950kg	600kg	950kg	1500kg	1500kg	1500kg	1500kg
油壓馬達(HP)	●	●	●	3HP	3HP	3HP	3HP	3HP	3HP	5HP	7.5HP	7.5HP	7.5HP	7.5HP	7.5HP	7.5HP
總用電壓	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V	220V/380V/440V
電源頻率	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz
最大製模面積 L x W	420x220	420x200	420x200	500x280	550x250	600(L)x350(W)	600(L)x350(W)	550x280	650(L)x350(W)	800(L)x300(W)	500x280	1000(L)x300(W)	1000x900	1550x300	2000mmx550mm	
外觀尺寸 L x W x H	1150(L)x1400(D)x2850(H)	1250(L)x1250(D)x2050(H)	1250(L)x1250(D)x2050(H)	1580(L)x1650(D)x2650(H)	1580(L)x1550(D)x2250(H)	1850(L)x1600(D)x2820(H)	1850(L)x1750(D)x2950(H)	1450(L)x1760(D)x2780(H)	1900(L)x1950(D)x2780(H)	1570(L)x1930(D)x2870(H)	2080(L)x1760(D)x2780(H)	1950(L)x1550(D)x2500(H)	1800(L)x2800(D)x2150(H)	2550(L)x1650(D)x3050(H)	3300(L)x2580(D)x2750(H)	
木箱尺寸 L x W x H	1300(L)x1600(D)x2400(H)	1450(L)x1400(D)x2200(H)	1450(L)x1400(D)x2200(H)	1700(L)x1800(D)x2400(H)	1700(L)x1700(D)x2400(H)	2100(L)x1850(D)x2500(H)	2100(L)x1950(D)x2500(H)	1650(L)x2000(D)x2400(H)	2100(L)x2100(D)x2500(H)	1670(L)x2050(D)x2500(H)	2200(L)x2150(D)x2500(H)	2200(L)x1750(D)x2500(H)	2000(L)x3000(D)x2500(H)	2700(L)x1850(D)x2500(H)	3500(L)x2800(D)x2500(H)	
淨重	950kg	950kg	1200kg	1350kg	1350kg	1600kg	1600kg	1150kg	1800kg	1800kg	1800kg	1400kg	1400kg	2200kg	3600KG	